

**IN THE CLAIMS:**

1-3. (Cancelled)

4. (Previously presented) A compact optical tracking system for magnetic tape, comprising:
- a magnet head assembly;
  - a positioning actuator for changing the position of the magnetic head assembly;
  - and
  - an optical servo module structure for outputting a position signal to the positioning actuator, causing the positioning actuator to change a position of the magnetic head assembly, wherein the optical servo module structure comprises at least two optical servo modules, each comprising:
    - an optical beam source for emitting an optical beam;
    - at least a first and second detector for detecting an optical beam reflection, wherein the first detector detects a first spot and the second detector detects a second spot, the second spot being offset from the first spot in a transverse direction by approximately one-quarter of a track spacing between successive tracks on the recording medium; and
    - an optical beam interference composition for interfering with the optical beam and producing a predetermined pattern on a target.

5-7. (Cancelled)

8. (Previously presented) A compact optical tracking system for magnetic tape, comprising:
- a magnetic head assembly;
  - a positioning actuator for changing the position of the magnetic head assembly;
  - and
  - an optical servo module structure for outputting a position signal to the positioning actuator, causing the positioning actuator to change a position of the magnetic head assembly, wherein the optical servo module structure comprises at least one optical servo module, comprising:

an optical beam source for emitting an optical beam;  
a detector for detecting an optical beam reflection; and  
an optical beam interference composition for interfering with the optical beam and producing a predetermined pattern on a target;  
wherein each optical servo module contains at least a first and second detector for detecting an optical beam reflection;  
wherein the optical servo module structure comprises a plurality of optical servo modules;  
further comprising a yoke assembly, wherein the optical servo module structure is affixed to a yoke assembly, and the optical servo module structure faces a back side of the magnetic tape;  
further comprising a grating assembly, wherein the grating assembly comprises at least one reference grating used as a target for the predetermined pattern emitted from the optical source within the optical servo module;  
further comprising an outboard reference grating on the grating assembly, wherein the outboard reference grating is affixed to the grating assembly past the extent of the magnetic tape;  
and  
an outboard servo module, wherein the predetermined pattern emitted from the optical source within the outboard servo module uses the outboard reference grating as a target.

9. (Original) The compact optical tracking system recited in claim 8, wherein the positioning actuator is configured between the yoke assembly and the magnetic head assembly, and wherein only the magnetic head assembly is moved by the positioning actuator.

10. (Original) The compact optical tracking system recited in claim 8, wherein the positioning actuator is configured adjacent to both the yoke assembly and the magnetic head assembly, wherein the yoke assembly and the magnetic head assembly are moved by the positioning actuator.

11. (Original) The compact optical tracking system recited in claim 8, wherein one of the reference grating and outboard reference grating contain a reference index on the reference grating.

12. (Original) The compact optical tracking system recited in claim 8, wherein the grating assembly is affixed to the magnetic head assembly between the read and write heads.
13. (Original) The compact optical tracking system recited in claim 8, wherein the outboard reference grating is affixed adjacent to one of the read and write heads.
14. (Original) The compact optical tracking system recited in claim 8, further comprising:  
a fine positioning actuator for adjusting the magnetic head assembly relative to one of the reference grating and the outboard reference grating.
15. (Original) The compact optical tracking system recited in claim 11, further comprising:  
a fine positioning actuator for adjusting the magnetic head assembly relative to the reference index on one of the reference grating and the outboard reference grating.
16. (Original) The compact optical tracking system recited in claim 8, further comprising:  
a linear actuator for loading magnetic tape onto the magnetic head assembly.
17. (Original) The compact optical tracking system recited in claim 8, further comprising:  
a rotary actuator for loading magnetic tape onto the magnetic head assembly.
- 18-26. (Cancelled)
27. (Currently amended) An optical tracking system for aligning a recording medium, comprising:  
at least one source of coherent electromagnetic radiation;  
an interference generating device;  
wherein the interference generating device causes ~~the superposition~~ superimposition of coherent radiation emitted from the at least one source to form at least two spots on the recording medium;  
wherein the two spots are formed at different distances from a track on the recording medium;

wherein the direction and magnitude of offset of the track is determined based on the relative locations of the at least two spots with respect to the track, wherein the at least two spots comprise a first group of spots and a second group of spots, wherein the intensity of the first group of spots is averaged and the intensity of the second group of spots is averaged.